

CELmar2-3


VHF Marine Antenna

CELmar2-3 is a lightweight fibreglass omnidirectional antenna. The CELmar2-3 is manufactured in premium quality materials in order to prevent galvanic corrosion. The antenna ferrule fits 1"-14TPI thread mounts directly.

CELmar2-3 is sold worldwide through more than three decades. The antenna is subject for improvement at all times. The antenna has the same rugged design as all other AC Antennas products thus it withstands harsh environmental conditions.

Electrical specifications:	
Frequency range (MHz)	156.0-162.5
Nominal impedance (ohm)	50
VHF power rating (Watt)	100
Gain (dBd/Marine dB)	0/3
VSWR	< 1.5:1
Polarization	Vertical
Connector	10m/32ft RG58C/U Cable
DC-shorted	No

Mechanical specifications:	
Length (m/ft)	1.04/3.4
Weight (kg/lbs)	0.7/1.6
Wind rating (m/s / mph)	45/101
Material	Fibreglass
Colour	Polyurethane lacquer
Temperature range (°C/°F)	-40 to +60 / -40 to +140
Ingress Protection	IP66



Mounting:

No mount included.

Can be used with all 1"-14TPI thread standard AC Antennas mounting equipment.

AC Antennas A/S · Fabriksparken 40 · DK-2600 Glostrup · DANMARK · VAT: DK25673786 Tel: +45 4581 0413 · Fax: +45 4581 0493 · acantennas@acantennas.com · www.acantennas.com